
## **ZECONS**




## Finger Print based Time Attendance & Access Control Solutions





Parameters	CA 202 – FP
Controller	RISC & DSP processor based
Communication	Integrated Onboard TCP-IP @ 10/100 mbps
interface	
Access modes	Either (i) Card + Finger (ii) PIN + Finger (iii) Card only (iv) Finger only.
Card options	Proximity card / Smart card
Card Read range	Upto 50 mm depending on the environmental EM conditions
Finger print sensor	Optical type
Template Storage	9000 finger print templates (384 bytes per template)
Enrollment time	4 seconds
Verification time	<1 second when used in the following access modes: Card + Finger / PIN + Finger / Card only
False Acceptance rate	1 in 10,000 (programmable for each template)
False Rejection rate	1 in 1,000
Configurable	Yes
percentage of	
Fingerprint matching	
Fingerprint	± 30° with Finger Guide provided
displacement	
Display / Indication	2 X 16 character LCD with backlit
Memory	Flash 512 KB supports 5000 E.mask entries and 10,400 employee data storage
Keypad	Yes
Data capture	Online / Offline downloading
IN/OUT Read mode	Switch / Software / Additional card reader
selection	
Data retention	RTC with battery backup (for upto 5 years)
Other features	Firmware updation via LAN network
	▶ 4 Relay outputs and 4 Feed back signal for Access Control
	➤ Spare 4 Nos. of I/O signals
	> Parallel port for Printer Interface by default
	> Onboard eight channel A/D converter and comparators for logical
	operation  Multi-user emplication seftwere in Windows under MS Assess/ Oracle/
	Multi-user application software in Windows under MS Access/ Oracle/
	SQL capable of generating more than 100 reports including daily, weekly, monthly reports.
	Titionining reports.

Parameters	CA 202 – FP
Electrical Features	<ul> <li>Voltage 230 V AC Standard and 110V AC optional</li> <li>Rechargeable battery backup for 8 hours operation</li> <li>Power 5 VA typical</li> </ul>
Physical Characteristics  > Dimension  > Mounting type  > Weight	> 170 (H) x 205 (W) x 90 (D) in mm > Wall mounting with hooks > 1.5 kg approx.
Environmental Conditions > Operating temperature > Humidity	> 0 to 50° C > 0% to 95% non condensing



Disclaimer: Finger Print enrollment and verification results are subject to FP quality of individuals. For those FP reading is not consistent, we recommend card only option.

## Zenith Controls & Systems Pvt. Ltd.

# 18, 4<sup>th</sup> Cross, 5<sup>th</sup> Block, Industrial Layout, Koramangala, Bangalore – 560 095. Tel: 4083 9800 (10 Lines) Fax: 25532304, e-mail: sales@zecons.com

## **BRANCHES**

Chennai : 28273425, 28223336, 93810-26637, 98405-73684, zeconschn@satyam.net.in

Cochin : 98958-10355, 98463-63007, zeconskch@rediffmail.com

Coimbatore : 2492164, 2498051, <u>zeconscbe@satyam.net.in</u>
Delhi : 22488404, 98683-42172, <u>zecons@bol.net.in</u>

Hyderabad : 27811425, 27816379, 93930-09155, <u>zeconshyd@satyam.net.in</u>
Kolkata : 24210922, 98300-77734, 98307-54955, <u>zeconscal@rediffmail.com</u>

Madurai : 2681215, 94439-18811, zeconsmadurai@yahoo.com

Mumbai : 98332-10955, Francise shank@yahoo.com
Mysore : 98454-26658, nbalaji1980@rediffmail.com
Nashik : 98222-87083, zecons@in.bosch.com