

uFace 602



## ➔ Multi-Biometric T&A and Access Control System

Face capacity : 1,200 (3000 Optional) 1:N  
Fingerprints templates : 2000  
Card Storage : 10,000 (optional)  
Transaction storage : 1,00,000  
Card reader : Yes  
CPU : 1.0GHz  
Fingerprint sensor : 500 DPI Optical sensor  
FAR :  $\leq 0.0001\%$   
FRR :  $\leq 1\%$   
Identification speed :  $< 0.5$  sec  
Algorithm Ver : 10  
Display : 4.3-Inch Touch Screen  
Keypad : 4 x 4 with 5 function Keys  
LED Indicator : Green/Red  
Schedule Bell/Speaker : Mini Speaker  
Communication : TCP/IP, RS232/485, USB Host  
Push data : Yes  
Power Supply : 12V 3A  
Operating Temperature : 0 °C - 45 °C  
Operating Humidity : 20% - 80%  
Dimension : 194.1x169x109.0mm  
Wiegand : Output

Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock

Support Fire Alarm : Yes

Door Sensor : Yes

Anti Passback : Yes

Door Bell : Yes

Support exit readers : No

Battery : 7.4 V, 2000 mAh Backup Battery

### Compatible :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

### Compatible Software and SDK:

- Smart office suite desktop and web
  - etime track lite desktop & web
  - SDK for desktop applications
  - Web based Device Manager/ePush server using Push data.
- Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications